

L72★ - ★★ - ★★★

Type	Port	Thread Form	Air Flow Direction	Drain	Bowl	Options
C Oil-Fog	2 1/4"	A PTF	P Uni-directional	E Closed bottom	D Short metal with liquid level indicator	N None
M Micro-Fog	3 3/8"	B ISO Rc taper		Q Manual, 1/4 turn	T Short transparent without guard	P Pyrex sight-feed dome
		G ISO G parallel			L Long transparent without guard	
					W Long transparent with guard	

TECHNICAL DATA

Fluid: Compressed air
 Maximum pressure:
 Transparent bowl: 10 bar (150 psig)
 Metal bowl: 17 bar (250 psig)
 Operating temperature*:
 Transparent bowl: -20° to +50°C (0° to +125°F)
 Metal bowl: -20° to +65°C (0° to +150°F)
 * Air supply must be dry enough to avoid ice formation at temperatures below +2°C (+35°F).
 Start point (minimum flow required for lubricator operation) at 6,3 bar (90 psig) inlet pressure:
 Oil-Fog models: 0,5 dm³/s (1.0 scfm)
 Micro-Fog models: 0,9 dm³/s (2.0 scfm)
 Typical flow with 6,3 bar (90 psig) inlet pressure and 0,5 bar (7 psig) pressure drop: 24 dm³/s (51 scfm)
 Nominal bowl size:
 Short bowl: 56 ml (1.9 fluid ounce)
 Long bowl: 65 ml (2.2 fluid ounce)
 Manual drain connection: 1/8"
 Materials:
 Body: Zinc
 Bowl:
 Transparent: Polycarbonate
 Transparent with guard: Polycarbonate, steel guard
 Metal: Zinc
 Metal bowl liquid level indicator lens Transparent nylon
 Sight-Feed dome: Transparent nylon
 Elastomers: Neoprene, nitrile, and Geolast®

REPLACEMENT ITEMS

Service kit (includes items circled on exploded view)	4382-500
Liquid level lens kit (25, 27, 28, 29)	4380-030
Manual drain (9, 10, 11) (16, 17, 18) (22, 23, 24)	619-50

INSTALLATION

- Shut off air pressure. Install filter/regulator in air line
 - vertically (reservoir down),
 - with air flow in direction of arrow on body,
 - downstream of filters and regulators,
 - upstream of cycling valves,
 - as close as possible to the device being lubricated,
 - Oil-Fog Models - Not more than 5,2m (15 feet) from the device being lubricated, and at the same height or higher than the device.
- Connect piping to proper ports using pipe thread sealant on male threads only. Do not allow sealant to enter interior of regulator.
- Push reservoir, or reservoir with guard, into body and turn fully clockwise before pressurizing.

RECOMMENDED LUBRICANTS

Fill reservoir with a good quality, light, misting type oil for compressed air tools. See Norgren publication N/AL.8.900.935. Fill to maximum fill line on transparent reservoirs. Oil level must always be visible in lens on metal reservoirs. DO NOT OVERFILL.

FILL RESERVOIR (OIL-FOG LUBRICATORS)

Remove fill plug (2), add oil, and reinstall fill plug. Fill plug can be removed and oil added without shutting off air pressure to the lubricator.

FILL RESERVOIR (MICRO-FOG LUBRICATORS)

Shut off inlet air pressure and reduce pressure in reservoir to zero. Remove fill plug (2), add oil, and reinstall fill plug. Do not remove the fill plug when the reservoir is pressurized, as oil will blow out the fill plug hole.

ADJUSTMENT

- Turn on system pressure.
- Adjust lubricator drip rate only when there is a constant rate of air flow thru the lubricator. Monitor drip rate thru sight feed dome (4).

- Oil-Fog Lubricators - Determine the average rate of flow thru the lubricator. Turn slotted green rotator in sight feed dome (4) to obtain one drop per minute for each 5 dm³/s (10 scfm). For example, if the average flow is 19 dm³/s (40 scfm), set the drip rate at 4 drops per minute. Turn rotator counterclockwise to increase and clockwise to decrease the drip rate. Total travel of rotator is 320°.
 - Micro-Fog Lubricators - Determine the average rate of flow thru the lubricator. Turn slotted red rotator in sight feed dome (4) to obtain the recommended drops per minute. See Drip Rate Chart. Turn rotator counterclockwise to increase and clockwise to decrease the drip rate. Total travel of rotator is 320°.
- Drip Rate Chart for Micro-Fog Lubricators
- | Flow - dm ³ /s (scfm) | Drops per Minute |
|----------------------------------|------------------|
| 0,9 to 2,4 (2 to 5) | 7 |
| 2,4 to 14,2 (5 to 30) | 8 |
| 14,2 to 18,9 (30 to 40) | 9 |
- Monitor the device being lubricated for a few days following initial adjustment. Adjust the drip rate if the oil delivery at the device appears either excessive or low.

DISASSEMBLY

- Shut off inlet pressure. Reduce pressure in inlet and outlet lines to zero. Loosen fill plug (2).
- Remove reservoir - push into body and turn counterclockwise.
- Disassemble in general accordance with the item numbers on exploded view. Do not remove the manual drain unless replacement is necessary. Remove and replace drain assembly only if drain malfunctions. Do not remove siphon tube (36). Remove and replace items 31 thru 35 only if lubricator malfunctions.

CLEANING

- Clean plastic reservoir with warm water only. Clean other parts using warm water and soap.
- Dry parts. Blow out internal passages in body with clean, dry compressed air.
- Inspect parts. Replace parts found to be damaged. If plastic reservoir shows signs of cracking or cloudiness, replace with a metal reservoir.

ASSEMBLY

- Lubricate o-rings, the portion of the manual drain body (9, 16, 22) that contacts the bowl, and the hole in the manual drain body that accommodates the stem of drain valve (10, 17, 23) with o-ring grease.
- Assemble the unit as shown on the exploded view.
- Torque Table

Item	Torque in Nm (Inch-Pounds)
2 (Fill plug)	1,0 to 1,2 (9 to 11)
4, 6 (Dome) and 24A (Nut)	2,3 to 2,8 (20 to 25)
25 (Screw)	1,9 to 2,5 (17 to 22)
31 (Screw)	0,7 to 0,9 (6 to 8)
- Push reservoir, or reservoir with guard, into body and turn fully clockwise.

WARNING

These products are intended for use in industrial compressed air systems only. Do not use these products where pressures and temperatures can exceed those listed under Technical Data.

Polycarbonate plastic reservoirs can be damaged and possibly burst if exposed to such substances as certain solvents, strong alkalis, compressor oils containing esterbased additives or synthetic oils. Fumes of these substances in contact with the polycarbonate reservoir, externally or internally, can also result in damage. Clean with warm water only

Use metal reservoir in applications where a plastic reservoir might be exposed to substances that are incompatible with polycarbonate.

In lubrication applications some oil mist may escape from the point of use to the surrounding atmosphere. Users are referred to safety and health standards for limiting oil mist contamination and utilization of protecting equipment

Before using these products with fluids other than air, for nonindustrial applications, or for life-support systems consult Norgren.

